

12

EUROPEAN PATENT APPLICATION

21 Application number: 89108105.1

51 Int. Cl.4: **A61B 17/22**

22 Date of filing: 05.05.89

30 Priority: 17.05.88 JP 64020/88 U
 05.04.89 JP 39629/89 U

43 Date of publication of application:
 23.11.89 Bulletin 89/47

84 Designated Contracting States:
 DE ES FR GB IT NL SE

71 Applicant: **SUMITOMO BAKELITE COMPANY LIMITED**
 11-36 Mita-3-chome Minato-ku
 Tokyo(JP)

72 Inventor: Inoue, Naohiko
 32-36, Hirado-2-chome
 Totsuka-ku Yokohama(JP)
 Inventor: Noguchi, Yasuo
 Neokopo Totsuka 709, 70-17, Nasecho
 Totsuka-ku Yokohama(JP)

74 Representative: Henkel, Feller, Hänzeler & Partner
 Möhlstrasse 37
 D-8000 München 80(DE)

54 A horn used in an ultrasonic surgical operating instrument.

57 A horn (1) used in an ultrasonic surgical operating instrument for crushing and removing organic tissue comprises a horn body (10) vibrated by ultrasonic vibration source for crushing the organic tissue, a removing passage (20, 21, 22; 23) extending through the horn body, through which the crushed tissue is removed outside, a bulkhead (30) disposed in the removing passage, and at least one through hole (31, 32, 33, 34, 35, 36) formed in the bulkhead. The bulkhead and the hole cooperate with each other to reduce a cross-sectional area the removing passage.

FIG. 1A





FIG. 1B



Xerox Copy Centre

EP 0 342 448 A1

A HORN USED IN AN ULTRASONIC SURGICAL OPERATING INSTRUMENT

FIELD OF THE INVENTION AND RELATED ART STATEMENT

The present invention relates to a horn used in an ultrasonic surgical operating instrument, and more particularly to a horn for crushing and removing organic tissue.

Recently, an ultrasonic surgical instrument, e.g. an ultrasonic operating scalpel, has been used in various surgical operations. The ultrasonic surgical instrument utilizes a mechanical vibration caused by an ultrasonic source for crushing and emulsifying organic tissue, and removes the crushed tissue outside. A horn in the ultrasonic surgical instrument is connected at one end thereof with the ultrasonic source. Mechanical vibration caused by the ultrasonic source is transmitted to an operating portion of the horn located on the other end portion thereof. The operating portion of the horn vibrates to crush the tissue, which abuts on the organic tissue to be treated. The crushed tissue is removed outside of the horn through a passage formed in the horn. The passage generally opens at the other end of the horn and has a uniform cross-sectional area. Accordingly, it becomes the problem that the tissue is insufficiently and roughly crushed by the operating portion and then coarse crushed tissue pieces clog the passage.

OBJECT AND SUMMARY OF THE INVENTION

An object of the present invention is to provide a horn capable of efficiently crushing and removing organic tissue without clogging the passage formed in the horn.

To this end, according to the present invention, provided is a horn for crushing and removing organic tissue comprising, a horn body vibrated by ultrasonic vibration source, passage means extending through the horn body, and means for reducing a cross-sectional dimension of the passage means.

Other objects and the advantages of the present invention will become apparent from the following description of the preferred embodiments explained with referring to the accompanying drawings attached hereto.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1A is a side view of a horn according to a first embodiment of the present invention;

Fig. 1B is a sectional view of the horn taken along the line B-B in Fig. 1A;

Fig. 2A is a side view of a horn according to a second embodiment;

Fig. 2B is a sectional view of the horn taken along the line B-B in Fig. 2A;

Fig. 3A is a side view of a horn according to a third embodiment;

Fig. 3B is a fragmentary sectional view of the horn taken along the line B-B in Fig. 3A;

Fig. 4A is a side view of a horn according to a fourth embodiment;

Fig. 4B is a fragmentary sectional view of the horn taken along the line B-B in Fig. 4A;

Fig. 5A is a side view of a horn according to a fifth embodiment; Fig. 5B is a fragmentary sectional view of the horn taken along the line B-B in Fig. 5A;

Fig. 6A is a side view of a horn according to a sixth embodiment;

Fig. 6B is a fragmentary sectional view of the horn taken along the line B-B in Fig. 6A;

Fig. 7A is a side view of a horn according to a prior art; and

Fig. 7B is a sectional view of the horn taken along the line B-B in Fig. 7B.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In a first embodiment shown in Figs. 1A and 1B, a horn 1 includes a horn body 10 having at one end portion thereof a radially enlarged part 11. The horn body 10 may be made of metal having a corrosion resistance, such as titanium or aluminium alloy and stainless steel. The horn body 10 is provided therein with a straight suction passage 20 extending axially therethrough. The horn body 10 is to be connected at one end thereof with an ultrasonic transducer which acts as an ultrasonic vibration source. The connection between the horn body 10 and the transducer is to be conducted by means of screw coupling through a thread portion 12 formed in an inner wall of the passage 20. On the connection, the transducer is so connected to the horn body 10 that a through passage formed in the transducer coincides with the passage 20.

A bulkhead 30 is located in the passage 20 and is integrally formed with an end of the other end portion 13 of the horn body 10. The bulkhead 30 is provided with a plurality of small through holes 31. These holes 31 serve to reduce a cross-sectional area of the passage 20. The bulkhead 30 has a thickness of 0.5 mm to 25 mm, preferably 1 mm to 10 mm.

An operation of the above-mentioned embodi-

ment will be described hereinafter.

At first, the horn 1 is so positioned that the end portion 13, so called an operating portion 13, abuts on the organic tissue to be treated. Thereafter, a driving power is supplied to the transducer to reciprocate or vibrate the horn body 1. Accordingly the operating portion 13 of the horn body 10 crushes and emulsifies the organic tissue. Simultaneously cleaning liquid agent is usually applied towards the operating portion 13. The horn 1 removes the crushed and emulsified organic tissue, and the cleaning liquid agent or a body fluid outside of the horn 1 through the passage 20.

In this embodiment, since the cross-sectional area of the passage 20 is once reduced by the holes 31 formed in the bulkhead 30, the only fine crushed tissue can pass into the passage 20 through the holes 31. No coarse crushed tissue pieces can pass through the holes 31 to clog the passage 20. Further the bulkhead 30 serves to increase a contact area of the horn body 10 against the tissue. Therefore crushing efficiency of the horn 1 is extremely raised. To the contrary, in the prior art, as shown in Figs. 7A and 7B, since the passage 200 is uniform in a cross-sectional area thereof, coarse crushed tissue pieces can be sucked into the passage 200 to clog it.

The material of the horn body 10 may not be limited to ones described above. Another material is applicable, which has a sufficient strength against the ultrasonic vibration having a propagation speed of 1000 m/s to 6000 m/s. These are, for example, the carbon fiber reinforced metal composed of metal (e.g. aluminum) and the carbon fiber, and a carbon fiber reinforced plastic composed of plastic (e.g. polysulfone) and carbon fiber. Further graphite is also applicable.

In the first embodiment, a plurality of small holes 31 are provided in the bulkhead 30. However, even though a single hole is provided in the bulkhead 30 instead of the holes 31, the same advantages can be enjoyed.

Referring to Figs. 2A and 2B, a second embodiment has a bent suction passage 21 opening at a side wall of the enlarged part 11. The crushed and emulsified organic tissue is removed outside through a metal or a plastic tube communicated to the side wall opening 21s. The ultrasonic transducer is to be attached to one end of the enlarged part 11 of the horn body 10 through a thread portion 12 formed therein.

It should be noted that a cross-sectional shape of the hole in the bulkhead is not limited to a circular. As shown in Figs. 3A and 3B, a plurality of holes each having an elliptic cross-section are applicable. Further a polygonal cross-sectional aperture or a poly-edgings cross-sectional aperture 33 is also applicable as shown in Figs. 4A and 4B.

Referring to Figs. 5A and 5B, another embodiment has a bulkhead 30 disposed apart somewhat from the operating portion 13, which divides the passage into two parts 22 and 23. The bulkhead 30 is provided therein with an aperture 34 which extends through the bulkhead 30 and having a cross-sectional area smaller than that of the passage. According to this embodiment, a further fine crushing of the tissue can be obtained. Namely, the organic tissue is roughly crushed first by the operating portion 13 and received within the passage part 22. In the passage part 22, the coarse crushed tissue pieces collide with an end face 30i of the bulkhead 30 to be further crushed to fine pieces. The fine pieces of the tissue pass into the passage part 23 through the aperture 34, without clogging of the passage part 23.

When the fragile tissue is crushed, it may be possible for the fragile tissue to scatter around to contaminate or damage the neighboring tissue. In this embodiment, an inner wall 13 of the operating portion 13 prevents the pieces of tissue crushed by the bulkhead 30 from scattering outwards. Accordingly, if this horn is applied to the fragile tissue, e.g. calcium tissue, it is prevented that the crushed tissue scatters around to damage the neighboring tissue.

Though an axial length of the passage part 22 varies according to an amplitude of ultrasonic vibration source supplied to the horn, the length is 0.1 mm to 30mm, preferably 1 mm to 15 mm.

It should be noted that a plurality of small apertures may be formed in the bulkhead 30 instead of a single aperture. In this case, the same advantages as the above mentioned can be also enjoyed. The dimensions of the apertures 35 and 36 may be different from each other as shown in Figs. 6A and 6B.

Claims

1. A horn (1) used in an ultrasonic surgical operating instrument for crushing and removing organic tissue, said horn comprising:
a horn body (10) for crushing said organic tissue, which is vibrated by ultrasonic vibration source;
passage means (20, 21, 22, 23) extending through said horn body, through which the crushed tissue is removed outside; and
means (30, 31) provided within said passage means for reducing a cross-sectional dimension of a location of said passage means in which said reducing means is disposed.

2 A horn according to Claim 1, wherein said reducing means includes a bulkhead (30) disposed in said passage means and aperture means (31, 32, 33, 34, 35, 36) axially extending through said bulkhead.

5

3. A horn according to Claim 2, wherein said bulkhead is disposed in one end of said passage means.

4. A horn according to Claim 2, wherein said bulkhead is disposed in a midway through said passage means.

10

5. A horn according to Claim 2, wherein said aperture means includes at least one through hole.

6. A horn according to Claim 5, wherein said hole (31, 32, 34, 35, 36) has a circular or an elliptic cross-section.

15

7. A horn according to Claim 5, wherein said hole (33) has a polygonal cross-section.

8. A horn according to Claim 5, wherein said hole (33) has a poly-edgings cross-section.

20

25

30

35

40

45

50

55

4







FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7A
PRIOR ART





FIG. 7B
PRIOR ART





DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
X	DE-A-3 707 921 (OLYMPUS) * Column 12, lines 18-22; figure 25 *	1	A 61 B 17/22
Y	---	2,3,5	
Y	US-A-4 045 859 (COOLEY et al.) * Column 3, lines 17-23; figure 2 *	2,3,5	
A	EP-A-0 001 718 (CHINOIN) * Page 12, lines 24-27; figures 3a,b *	7	
			TECHNICAL FIELDS SEARCHED (Int. Cl. 4)
			A 61 M A 61 B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 24-08-1989	Examiner MOERS R.J.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P0401)

THIS PAGE BLANK (USPTO)